

## **Certification Record**

CUSTOMER	CLASS	FILE
Warmly Yours.com, Inc.	<u>2872-81</u>	247310
2 Corporate Dr, Suite 100,	HEATERS-Cable and Cable Sets - Certified to US Standards	
Long Grove		
IL		
60047		
USA	Refer to Class Description for program details	

## TO THE REQUIREMENTS OF UL 515 AND IEEE 515.1-2005:

Series Heating Cable Sets, two-conductor constructions of:

- a) cat. nos. SHC (non-mat construction), and SHM (mat construction), indoor embedded floor warming (space heating cables installation beneath floors of enclosed structures), 20W/m maximum, 6000W maximum, rated at 500V maximum, maximum temperature rating 70°C.
- b) cat. nos. WHCS (non-mat construction) and WHMS (mat construction), outdoor embedded and roof and gutter de-icing (Installation Types B & C), 40 W/m maximum for embedded tracing and 18 W/m maximum for roof & gutter de-icing, 6000 W maximum, rated at 500 V maximum, maximum temperature rating  $70 ^{\circ}\text{C}$ .
- c) cat. nos. WHCA (non-mat construction) and WHMA (mat construction), outdoor embedded snow melting (Installation Type C), 40W/m maximum, 6000W maximum, rated at 500V maximum, maximum temperature rating 70°C.

## Notes:

- 1. Installation in accordance with the National Electrical Code (NEC).
- 2. The Cat No may include suffixes to denote construction options.
- 3. The manufacturer's mimimum recommended installation temperature for these heating cable sets is -15°C.

/jj		
	Convright © 2010 CSA International. All rights reserved	